

Energy Decay of Solutions to a Nondegenerate Wave Equation with a Fractional Boundary Control

TAHRI Mohamed, BENKHEDDA Hanane and BENAÏSSA Abbes*

Laboratory of Analysis and Control of PDEs, Djillali Liabes University, P. O. Box 89, Sidi Bel Abbes 22000, Algeria.

Received 19 May 2020; Accepted 23 October 2020

Abstract. In this paper, we study the energy decay rate for a one-dimensional nondegenerate wave equation under a fractional control applied at the boundary. We proved the polynomial decay result with an estimation of the decay rates. Our result is established using the frequency-domain method and Borichev-Tomilov theorem.

AMS Subject Classifications: 93D15, 35B40, 47D03, 74D05

Chinese Library Classifications: O175.27

Key Words: Nondegenerate wave equation; fractional boundary control; Frequency domain method; Optimal polynomial stability.

1 Introduction

In this paper, we are concerned with the boundary stabilization of convolution type for nondegenerate wave equation of the form

$$w_{tt}(x,t) - (a(x)w_x(x,t))_x = 0 \text{ in } (0,1) \times (0,\infty), \quad (1.1)$$

where the coefficient a is a positive function on $[0,1]$.

Up to now, there are many works concerning the stabilization and controllability of nondegenerate wave equation with different types of dampings (see e.g. [1–4] and the references therein). In [4], for $a(x) = a_1x + a_0$: the authors have established asymptotic stabilization under boundary conditions of the form

$$\begin{cases} (aw_x)(0,t) = 0, \\ (aw_x)(1,t) = -kw(1,t) - w_t(1,t), \quad k > 0. \end{cases}$$

*Corresponding author. *Email addresses:* m_tahri5@yahoo.fr (M. Tahri), benkhedda-hanane@outlook.fr (H. Benkhedda), benaïssa_abbes@yahoo.com (A. Benaïssa)

It has been shown in [1], for $a \in H^1(0,1), a(x) \geq a_0 > 0$, that the feedback law

$$\begin{cases} (aw_x)(0,t) = -cw(0,t) - F(w_t(0,t)), & c > 0, \\ Mw_{tt}(1,t) + (aw_x)(1,t) = 0. \end{cases}$$

exponentially stabilizes equation (1.1) under appropriate assumptions on the function F . Another stabilization result for equation (1.1) has also been established in [3] via the action of the following feedback:

$$\begin{cases} (aw_x)(0,t) = -cw(0,t) - F(w_t(0,t)), \\ (aw_x)(1,t) = -cw(1,t) - F(w_t(1,t)), & c > 0. \end{cases}$$

In [2], the authors considered the following modelization of a flexible torque arm controlled by two feedbacks depending only on the boundary velocities:

$$\begin{cases} w_{tt}(x,t) - (a(x)w_x)_x + \alpha w_t(x,t) + \beta w(x,t) = 0, & 0 < x < 1, t > 0, \\ (a(x)w_x)(0) = k_1 w_t(0,t), & t > 0, \\ (a(x)w_x)(1) = -k_2 w_t(1,t), & t > 0, \end{cases}$$

where

$$\begin{cases} \alpha \geq 0, \beta > 0, k_1, k_2 \geq 0, k_1 + k_2 \neq 0, \\ a \in W^{1,\infty}(0,1), a(x) \geq a_0 > 0 \text{ for all } x \in [0,1]. \end{cases}$$

They proved the exponential decay of the solutions.

Motivated by the work of [2], a feedback control depending only on the velocity has been proposed in [5] for the system (1.1) and an asymptotic convergence result has been established (see also [6–8]).

In this article, we are concerned with the system

$$\begin{cases} w_{tt}(x,t) - (a(x)w_x(x,t))_x = 0, & \text{in } (0,1) \times (0,+\infty), \\ w(0,t) = 0, & \text{on } (0,+\infty), \\ (aw_x)(1,t) = -\rho \partial_t^{\alpha,\eta} w(1,t), & \text{on } (0,+\infty), \\ w(x,0) = w_0(x), w_t(x,0) = w_1(x), & \text{on } (0,1), \end{cases} \quad (P)$$

where $\rho > 0$. The notation $\partial_t^{\alpha,\eta}$ stands for the generalized Caputo's fractional derivative (see [9] and [10]) defined by the following formula:

$$\partial_t^{\alpha,\eta} f(t) = \frac{1}{\Gamma(1-\alpha)} \int_0^t (t-s)^{-\alpha} e^{-\eta(t-s)} \frac{df}{ds}(s) ds, \quad \eta \geq 0,$$

where Γ is the usual Euler gamma function and $(0 < \alpha < 1)$.

Although there is quite a bit of work on damping mechanisms for beam models of this kind, there does not seem to be much about damping involving fractional derivatives. In [11], Mbodje studies the energy decay of the wave equation (with $a \equiv 1$) with a